

## Mammut Selection

The special design of the Magicfloor Mammut vinyl tiles is provided by their different tile size which is larger than the usual standard size. The saw emboss type naturally imitates the natural surface of wood.

The easy installation and the total thickness of 2.5 mm both makes this type suitable for commercial and home application, as well.

### Specification according to EN 649

Characteristics	Standard	Unit	Result
Type of flooring	EN 649		synthetic floor covering with PUR heterogeneous, fiberglass reinforced
Plastics basis			Polyvinylchloride
Surface			different embossings

### Safety Criteria

Flammability	EN 13501-1	class	B <sub>n</sub> - s1
Slip resistance	BGR 181	group	R 9
Dynamic coefficient of friction	EN 13893	class	DS
Impact sound reduction	ISO 140-8	dB	9

### General properties

			wood	stone	mammut
Tiles: side length	EN 427	cm	91,4 x 15,2	45,7 x 45,7	122 x 30,5
Overall thickness	EN 428	mm	2.50		
Thickness of wear layer	EN 685	mm	0,55		
Total weight	EN 430	g / m <sup>2</sup>	4000		
Residual indentation	EN 433	mm	app. 0.04		
Colour fastness	ISO 105-B02	rating	≥ 6		
Wear group	EN 649		T		
Vertical resistance	EN 1081	Ohm	-		
Electrical insulation to ground	VDE 0100	kOhm	> 200		
Static electrical charge	EN 1815	kV	app. 2.0(antistatic)		
Thermal resistance	EN 12667	m <sup>2</sup> K / W	0.070		
Thermal conductivity	EN 12524	W/ m K	0.25		
Furniture leg	EN 424		No damage		
Castor chair	EN425		No damage		
Chemical resistance	EN 423		High resistance		



MAGICFLOOR<sup>®</sup>  
INTERNATIONAL

*The best way to your floor*



**11311 Light Brown**



**11312 Dark Brown**



**11314 Dark Grey**



**11315 light grey**



**11301 rusty brown**



**VINYL FLOORS**