

Stone Selection

Magicfloor Stone vinyl floors combine the advantages of resilient floors and stone design, too. The most important feature of the Stone Selection is that although its pattern imitates stone designs, it still offers the comfort of resilient floors. Stone Selection is suitable both for residential and commercial areas.

Specification according to EN 649

Characteristics	Standard	Unit	Result
Type of flooring	EN 649		synthetic floor covering with PUR heterogeneous, fiberglass reinforced
Plastics basis			Polyvinylchloride
Surface			different embossings

Safety Criteria

Flammability	EN 13501-1	class	B _n - s1
Slip resistance	BGR 181	group	R 9
Dynamic coefficient of friction	EN 13893	class	DS
Impact sound reduction	ISO 140-8	dB	9

General properties

			wood	stone	mammut
Tiles: side length	EN 427	cm	91,4 x 15,2	45,7 x 45,7	122 x 30,5
Overall thickness	EN 428	mm	2.50		
Thickness of wear layer	EN 685	mm	0,55		
Total weight	EN 430	g / m ²	4000		
Residual indentation	EN 433	mm	app. 0.04		
Colour fastness	ISO 105-B02	rating	≥ 6		
Wear group	EN 649		T		
Vertical resistance	EN 1081	Ohm	-		
Electrical insulation to ground	VDE 0100	kOhm	> 200		
Static electrical charge	EN 1815	kV	app. 2.0(antistatic)		
Thermal resistance	EN 12667	m ² K / W	0.070		
Thermal conductivity	EN 12524	W/ m K	0. 25		
Furniture leg	EN 424		No damage		
Castor chair	EN425		No damage		
Chemical resistance	EN 423		High resistance		





50201 - Stone Design Creamy



50203 - Stone Design Red Copper



50204 - Stone Design Brass



50205 - Stone Design Black Metallic

MAGICFLOOR[®]
INTERNATIONAL
The best way to your floor

VINYL FLOORS

